

PROLINE® ATMOSPHERIC VENT



Dynaclean™ Diffuser Dip Tube

Coregard™ Anode Rod

Push-Button Piezo Ignitor

Enhanced-Flow Brass Drain Valve

Heat Trap Nipple

Blue Diamond® Glass Coating

Code Compliance

- Meets UBC, CEC and HUD National Codes.
- Meets the efficiency requirements of the U.S. Department of Energy and current edition of ASHRAE/IES 90.1.

Design-Certified by CSA Group

- Certified at 300 psi test pressure and 150 psi working pressure. Listed according to ANSI Z21.10.1-CSA 4.1 standards governing storage tank-type gas water heaters.

6-Year Limited Tank and Parts Warranty

- For complete information, consult written warranty or go to hotwater.com.



Model Number	Nominal Gallon Capacity	Rated Storage Volume	First Hour Rating (Gallons)	UEF	BTU Input Natural Gas	BTU Input Propane Gas	Recovery 90°F Rise Gallon Per Hour	Dimensions in Inches				Approx. Shipping Weight (lbs)
								Height to Top of Draft Hood	Height to Top of Tank	Diameter	Draft Hood Outlet	
Tall Models												
†GCB-30	30	29	69	0.61	35,500	32,000	37	61-1/2	58	16	3 or 4	123
GCR-30	30	29	69	0.60	35,500	32,000	37	61-1/2	58	18	3 or 4	132
‡GCRH-40	40	38	65	0.61	35,500	N/A	38	61-3/4	58-1/4	20	3 or 4	138
†GCB-40	40	38	78	0.65	40,000	36,000	42	61-3/4	58-1/4	18	3 or 4	130
GCR-40*	40	38	80	0.66	40,000	36,000	42	61-3/4	58-1/4	20	3 or 4	138
GCG-50*	50	48	81	0.62	40,000	37,000	41	60-3/4	57-1/4	21	3 or 4	148
GCR-50*	50	48	84	0.62	40,000	37,000	43	60-3/4	57-1/4	22	3 or 4	165
GCRT-50*	50	48	89	0.61	50,000	45,000	54	60-3/4	57-1/4	22	4	165
†GCRX-50*	50	49	99	0.61	60,000	54,000	65	65-1/2	61	22	4	190
GCRX-55*	55	55	83	0.62	60,000	54,000	65	59-3/4	55-1/4	24	4	185
Short Models												
†GCBL-30	30	28	68	0.58	35,500	32,000	37	50	46-1/2	18	3 or 4	110
GCR-30	30	28	66	0.59	35,500	32,000	36	50	46-1/2	20	3 or 4	118
†GCBL-40	40	38	68	0.57	40,000	36,000	41	51-1/2	48	20	3 or 4	134
GCR-40	40	38	67	0.59	40,000	36,000	41	51-1/2	48	22	3 or 4	135
GCR-50	50	50	81	0.62	40,000	40,000	43	53-1/4	49-3/4	24	3 or 4	177

Water connection is 3/4" on all models.

*For optional side-mounted recirculating taps, add "L" to the suffix (example: GCR-40L).

† Models ship with supplied insulation blanket.

For 10-year tank and 10-year parts warranty, change "G" to "X" in model number (example: XCR-30).

‡ LP models not available on GCRH-40.

All models approved for installation from sea level to 10,100 ft. elevation.